

# Docking Drawer™

## ETL Listed In-Drawer Electrical Outlets



Take control and clear clutter. Docking Drawer in-drawer electrical outlet solutions are perfect for today's connected homes, bathrooms, kitchens, drop zones, bars, locker rooms, offices and more. Use Docking Drawers wherever you seek to clear clutter and charge or power your devices.

- First and only ETL Listed in-drawer electrical outlet
- Interlocking safety features that cut power to the outlet to minimize risk
- Adjustable rear mount bracket allows for fine tuning and arm alignment
- Versatile mounting: left, right, horizontally or vertically
- Simple to specify and easy to install
  1. Confirm space behind drawer box
  2. Confirm width behind drawer box
  3. Confirm drawer box height
  4. Confirm drawer extension



**Slim**  
AC Outlets & USB Ports



**Style Flush**  
AC Outlets



**Slim USB**  
USB Ports



All outlets include: assembly, receptacle, power cord and installation manual

### CHARGING




**Slim (2 AC, 2 USB)**



**Slim USB (4 USB)**

Phones, Tablets, Laptops, USB Flashlights, USB Speakers

### POWERING






**Style Flush (2 AC/GFCI)**

Hair Dryers, Curling Irons, Flat Irons, Appliances, Items Requiring Full Power



# Docking Drawer™

| Application:                               | CHARGING  |                        |                        |  |       |                         | POWERING  |                       |       |       |
|--|---|------------------------|------------------------|--|-------|-------------------------|---|-----------------------|-------|-------|
| Outlet Type                                |  |                        |                        |  |       |                         |  |                       |       |       |
|  | Docking Drawer Slim (2 AC, 2 USB)   |                        |                        | Docking Drawer Slim USB (4 USB)  |       |                         | Style Drawer Flush (2 AC/GFCI)  |                       |       |       |
| Cabinet Depth                              | ≤ 24"   | ≤ 21"                  | ≤ 18"                  | ≤ 24"  | ≤ 24" | ≤ 21"                   | ≤ 18"   | ≤ 24"                 | ≤ 21" | ≤ 18" |
| Outlet Name                                | Docking Drawer 24 Slim  | Docking Drawer 21 Slim | Docking Drawer 18 Slim | Docking Drawer 24 Slim USB   |       | Style Drawer 24 Flush   | Style Drawer 21 Flush   | Style Drawer 18 Flush |       |       |
| Part No. White Finish                      | <b>161106</b>   | <b>161102</b>          | <b>161128</b>          | <b>n/a</b>   |       | <b>161124</b>           | <b>161120</b>   | <b>161132</b>         |       |       |
| Part No. Black Finish                      | <b>161104</b>   | <b>161100</b>          | <b>161126</b>          | <b>161108</b>  |       | <b>161122</b>           | <b>161118</b>   | <b>161130</b>         |       |       |
| <b>Cabinet Specifications:</b>             |   |                        |                        |  |       |                         |   |                       |       |       |
| Max. Drawer Extension                      | 21"   | 18"                    | 15"                    | 21"  |       | 20"                     | 17"   | 14"                   |       |       |
| Min. Width Behind Drawer Box               | ≥ 17 ½"   | ≥ 16"                  | ≥ 14 ½"                | ≥ 17 ½"  |       | ≥ 13 ½"                 | ≥ 12"   | ≥ 10 ½"               |       |       |
| Min. Space Behind Drawer Box               | 3"  | 3"                     | 3"                     | 3"   |       | 5"                      | 5"  | 5"                    |       |       |
| Min. Interior Drawer Box Height            | 2 ¾"  | 2 ¾"                   | 2 ¾"                   | 2 ¾"   |       | 4"                      | 4"  | 4"                    |       |       |
| <b>Charging Receptacle Specifications:</b> |   |                        |                        |  |       |                         |   |                       |       |       |
| Tamper Resistant                           | Yes   |                        |                        | n/a  |       | Yes                     |   |                       |       |       |
| 120V AC Outlets                            | 2   |                        |                        | 0  |       | n/a                     |   |                       |       |       |
| USB Ports                                  | 2   |                        |                        | 4  |       | n/a                     |   |                       |       |       |
| Max Current                                | AC: 3 amps @ 120 VAC<br>USB: 3.6 amps @ 5 VDC                                     |                        |                        | USB: 4.2 amps @ 5 VDC  |       | n/a                     |   |                       |       |       |
| <b>Powering Receptacle Specifications:</b> |   |                        |                        |  |       |                         |   |                       |       |       |
| Tamper Resistant                           | n/a   |                        |                        | n/a  |       | Yes                     |   |                       |       |       |
| 120V AC Outlets                            | n/a   |                        |                        | n/a  |       | 2                       |   |                       |       |       |
| GFCI                                       | n/a   |                        |                        | n/a  |       | Yes                     |   |                       |       |       |
| LED Indicator                              | n/a   |                        |                        | n/a  |       | Yes                     |   |                       |       |       |
| Max Current                                | n/a   |                        |                        | n/a  |       | 20 amps                 |   |                       |       |       |
| <b>Features:</b>                           |   |                        |                        |  |       |                         |   |                       |       |       |
| ETL Listed to UL962a                       | Yes   |                        |                        | Yes  |       | Yes                     |   |                       |       |       |
| ETL Listed to CSA-22.2                     | No  |                        |                        | Yes  |       | No                      |   |                       |       |       |
| Interlocking Safety Feature                | Circuit Breaker   |                        |                        | Circuit Breaker  |       | Manual Reset Thermostat |   |                       |       |       |
| Electrical Connection                      | NEMA 5-15P  |                        |                        | NEMA 5-15P   |       | Hardwired               |   |                       |       |       |
| Warranty                                   | 1 Year  |                        |                        | 1 Year   |       | 1 Year                  |   |                       |       |       |